



Features :

- Independent electrical cabinet,not suitable for combined cabinet use.
- The Rear panel can be removed for easy work operation.
- The door panel is about 25mm off the ground to ensure flexible and smooth door opening.
- The main frame formed by the integral welding of the five-fold profiles can ensure the high strength.
- The reinforcing ribs of the square tube of the door panel can be fixed on the door with screws, which is easy to disassemble, and the frame is densely covered with 25mm spacing modular holes to ensure the flexibility of installation.

Custom Design Available :

- Custom sizes.
- Material/Material thickness.
- Lock/Hinge/Stiffener.
- Color(RAL).
- Custom Logo/Text.
- Pre-lasered cable entry holes & laser cut apertures.

Technical Data

Material	Enclosure frame(Roof,Side): Steel, 1.5 mm Rear plate: Steel, 1.5mm Door: Steel, 2.0 mm Mounting plate: Galvanized sheet, 2.0 mm Gland plates: Galvanized sheet, 1.5 mm Plinth: Steel, 1.5mm
Surface Reatment	Enclosure frame(Roof,Side), door,rear,panel are all Powder-Coated, RAL7035. Plinth is Powder-Coated, RAL7022
Protection Grade	Up to IP55 (acc.to GB64205-1993)
Installation	Freestanding with Plinth
Gasket	Door and rear panel: PU Foam Continuous Seal
Locking System	MS867 lock with key
Optional Items	Ventilation fan, Thermostat, Louvered Openings
Standard Approvals	IEC 60529 / EN 62208 / ISO 9001 / CE / RoHS

Standard Configuration

- Front door, Enclosure frame(Roof,Side), Mounting plate, Rear panel
- 1*MS867 lock
- 2*Longeron with 25mm hole pattern
- 4*Bearing suspension loop
- 2*Mounting strips on the door
- A4 data box on the doorpanel
- Lighting
- Door stopper

Regular Size

Model	Height1 (mm)	Height2 (mm)	Width (mm)	Depth (mm)
VES001	1800	100	800	600
VES002	1800	100	1000	600
VES003	1800	100	1200	600
VES004	2000	100	800	600
VPS005	2000	100	1000	600
VPS006	2000	100	1200	600

Note: Cabinets below 1000mm width are single-door type (hinge on the right side). Larger sizes are designed with double doors for easier access

