



Features:

- Made of cold rolled steel plate by bending and welding.
- Surface: Pre-treated with etching primer and finished with **RAL7035** polyester powder coating.
- Door panel PU sealing strip to prevent dust and rain from penetrating.
- Inlet and outlet holes are provided with hole cover plate (Sealing strip).
- Equipped with removable mounting plate.
- IP65 protection rating.
- Temperature Range:-40 C to 80 C.

Custom Design Available:

- Custom sizes.
- Material/Material thickness.
- Lock/Hinge/Stiffener.
- Color(RAL).
- Custom Logo/Text.
- Pre-lasered cable entry holes & laser cut apertures.

Technical Data

Material	Carbon Steel
Surface Reatment	Powder-Coated
Protection Grade	Up to IP65 (acc.to GB64205-1993)
Mounting Plate	Galvanized sheet,Removable
Color	RAL7035
Temperature Range	40 C to 80 C
Installation	Wall Mounting
Gasket	PU Foam Continuous Seal, Machine Foamed
Locking System	AB403 Lock with key
Earthing	Door and body with M6 earthing stud
Optional Items	Ventilation fan, Thermostat,Rainhood Louvered Openings,Inner door, Viewing Window
Standard & Approvals	IEC 60529 / EN 62208 / ISO 9001 / CE / RoHS
Standard Configuration	Mounting plate, Lock, Key, Earthing Screw

Model	Height(mm)	Width(mm)	Depth(mm)	Thickness(mm) <small>(Box body/Door plate/Mounting plate)</small>
VJ001	300	250	150	0.7/0.7/0.7
VJ002	400	300	150	0.7/0.7/0.7
VJ003	500	400	150	0.8/0.8/0.8
VJ004	400	300	200	0.7/0.7/0.7
VJ005	500	400	200	0.8/0.8/0.8
VJ006	600	400	200	0.8/0.8/0.8
VJ007	600	500	200	0.8/0.8/0.8
VJ008	700	500	200	0.8/0.8/0.8
VJ009	800	600	200	1.0/1.0/1.0
VJ010	1000	600	200	1.0/1.0/1.0
VJ011	1000	800	200	1.0/1.0/1.0
VJ012	500	400	250	0.8/0.8/0.8
VJ013	600	500	250	0.8/0.8/0.8
VJ014	700	500	250	0.8/0.8/0.8
VJ015	800	600	250	1.0/1.0/1.0
VJ016	1000	600	250	1.0/1.0/1.0
VJ017	1000	800	250	1.0/1.0/1.0
VJ018	500	400	300	0.8/0.8/0.8
VJ019	600	500	300	0.8/0.8/0.8
VJ020	800	600	300	1.0/1.0/1.0